

# ***STRONG***

# ***SRT 4950E***

## **HIGH DEFINITION DIGITAL SATELLITE RECEIVER**



- DVBS-2, MPEG4 Compliant
- DVR Function via USB Hard Drive (\* Not Supplied)
- Time Shift, Record & Playback
- Embedded Multicas Card Reader
- Advanced Blind Scan & Electronic Program Guide
- USB 2.0 Hosts (x2) for Wi-Fi Adaptor\*, USB-to-LAN converter, 3G Modem, Content Recording, Multi-media Playback and Software Update.
- Advanced easy to use menu
- RF Modulator, RS-232 & 2 x 2.0 USB Ports
- HDMI & Composite connections (Cables Included)
- Access IPTV, VOD, Youtube, Google Map, Weather via LAN, Wi-Fi or 3G

**Multimedia Playback  
& Record Function via USB\***

Technical Specifications - SRT 4950E



LNB / TUNER INPUT

- Frequency Range : 950Mhz - 2150MHz
- RF Input Signal Level : -25 ~ -65dBm
- RF Impedence : 75Ω
- LNB Power : 13/18V Max 400m A
- LNB Tone Switch : 22KHz +/- 2KHz, 0.65Vp-p+/-015V
- DiSeqC Control : Version 1.2 Compliant USALS
- Demodulation : QPSK, 8PSK
- Input Symbol Rate : DVB-S : 2~45 Ms/s. DVB-S2 : 10~30 Ms/s (QPSK. 8PSK)

MPEG TS A/V DECODER

- Transport Stream : DVBS-2 Compliant,
- Video : MPEG-2, MPEG-4, H.264
- Data Rate : up to 15M bits/s
- Audio : Mono, Stereo, Joint Stereo
- Aspect Ratio : 4:3, 16:9
- Video Resolution : 1920 x 1080p/i, 1280 x 720p, 720 x 576p/i
- Video Format : PAL
- Audio Mode : MPEG1 layer I/II, MPEG 2 layer II, AC3, Dolby Digital
- Audio Sampling Rates : 32, 44.1 and 48KHz

CONNECTORS

- LNB IF Input : IEC 169 - 24 Female
- LNB IF Loop-through : IEC 169 - 24 Femal
- HDMI : Digital Video / Audio Output
- RCA : Audio L/R x 2 Y/Pb/Pr x 3
- RF Modulator : IEC 169-2, female / male - Frequency 470 ~ 860Mhz

DATA PORTS

- USB : DC 5V Max 500mA ( x 2)
- Ethernet Port (LAN) : RJ 45
- RS-232 Serial : 9pin D-sub male approx 115K bps
- Wi-Fi : Wi-Fi via USB Dongle (not supplied)

POWER SUPPLY

- Input Voltage : AC 100V ~ 250V
- Power Consumption : max 24W
- Frequency : 50Hz ~60Hz

GENERAL DATA

- Size : 280 x 48x 185mm (W X H X D)
- Weight : 800Gms (unpacked)



STRONG AUSTRALIA PTY LTD - 60 WEDGEWOOD ROAD, HALLAM, VICTORIA, 3803 AUSTRALIA  
PH: +61 3 8795-7990 FAX: +61 3 8795-7991  
TECHNICAL SUPPORT: 1800 820 030 EMAIL: tech@strong.com.au  
SALES EMAIL: sales@strong.com.au

www.strong.com.au