

# STRONG

# SRT 4922B+

## HIGH DEFINITION DIGITAL SATELLITE RECEIVER



- DVBS-2, MPEG4 Compliant
- DVR Function via USB Hard Drive (\* Not Supplied)
- Time Shift, Record & Playback
- Embedded Conax CAS7 card reader
- Advanced Blind Scan
- Electronic Program Guide
- LAN Connection, Wi-Fi & 3G
- Advanced easy to use menu
- RF Modulator, 2 x 2.0 USB Ports
- HDMI & Composite connections
- Access IPTV, VOD, Youtube, Internet Radio, Maps, Flickr, Weather & Picasa via LAN, Wi-Fi or 3G

Multimedia Playback  
& Record Function via USB\*

# Technical Specifications - SRT 4922B+



## LNB / TUNER INPUT

Frequency Range : 950MHz - 2150MHz -65Dbm ~ -25Dbm dc  
Signal Level LNB : 13/18V, Max 400mA, 22KHz Ver  
Supply LNB Switch : 1.0 / 1.1 / 1.2/ USALS Compatible  
DiSeqC Control :  
Demodulation : Front End DVB-S/S2 QPSK, 8PSK, 16APSK, 32APSK  
Input Symbol Rate : DVB-S : 2~45 Msps / DVB-S2 : 1~30 Msps (QPSK) / 10~30Msps (8PSK)  
36Msps (16APSK) / 27Msps (32APSK)

## MPEG TS A/V DECODER

Transport Stream : DVB Compliant  
Video : MPEG-2, MPEG-4, H.264  
Data Rate : up to 15M bite/s  
Audio : Mono, Stereo, Joint Stereo  
Aspect Ratio : 4:3, 16:9  
Video Resolution : 1920 x 1080P/i, 1280 x 720P, 720 x 576P/i  
Video Format : PAL  
Audio Mode : MPEG1 layer I/II, MPEG 2 layer II, AC3, Dolby Digital  
Audio Sampling Rates : 32, 44.1 and 48KHz

## SYSTEM RESOURCES

Main Processor : 32Bit Processor (550MHz, 850DMIPS)      Flash ROM : 8Mbyte  
DDR DRAM : 127 Mbyte

## CONNECTORS

LNB IF Input : IEC 169 - 24  
LNB IF Loop-through : IEC 169 - 24  
HDMI : Digital Video / Audio Output  
RCA : Video - 1 x RCA cinch / Audio L/R 2 x RCA cinch  
RF Modulator : IEC 169-2, female / male - Frequency 470 ~ 860Mhz

## DATA PORTS

USB : DC 5V Max 500mA ( x 2)  
Ethernet Port (LAN) : RJ 45

## POWER SUPPLY

Input Voltage : AC 100V ~ 250V      Frequency : 50Hz ~60Hz  
Power Consumption : max 24W

## GENERAL DATA

Size : 250 x 45x 195mm (W X H X D)      Weight : 1.6Kg

STRONG AUSTRALIA PTY LTD - 60 WEDGEWOOD ROAD, HALLAM, VICTORIA, 3803 AUSTRALIA  
PH: +61 3 8795-7990      FAX: +61 3 8795-7991  
TECHNICAL SUPPORT: 1800 820 030      EMAIL: tech@strong.com.au  
SALES EMAIL: sales@strong.com.au

[www.strong.com.au](http://www.strong.com.au)